

ABS Mustang Headliner Installation Instructions

AFH31, AFH31S, AFH32, AFH32S & AFH32A 1979-93 Coupe, Hatchback and Sunroof

Please read these instructions completely through before starting the installation.

Note: All ABS Headliner boards come with pre-cut holes in the board for dome lights, visor bracket openings, etc. Fabric will cover the entire board. Once you choose which openings you need, using a razor knife, cut an "X" in the center of each opening and fold back the material that can be glued or taped to the back side of the board. This will give each opening a clean appearance.

1. Remove sunvisors, rear dome light & plastic trim moldings around the headliner. If present the old headliner should be removed and discarded. Note: The old headliner can be used as a reference in case there are some adjustments to be made.

Note: The Dome Light location for 1979 to 1984 should be 25-3/4" back from the front edge of the headliner to the center of the dome light area.

The Dome Light location for 1985 to 1993 should be 23-3/4" back from the front edge of the headliner to the center of the dome light area.

Note: The Dome Light opening for 1992-93 is slightly larger than the Dome Light opening for previous years. If you have your old headliner, use it for a template by laying it over the back side of the new headliner and drawing the dome light opening.

Please note that there is a dome light opening cut out already and to enlarge this hole will require the use of tin snips or a hack saw blade. Be careful cutting the fabric so that you don't cut too far. Once the Dome Light is installed, the Dome Light frame should cover up all edges and give your headliner a clean appearance.

2. Install headliner with the sunvisors loosely to hold the headliner in place in case there are some minor adjustments. Then re-attach the dome light and trim moldings. Once the headliner is in position, tighten down the sunvisor brackets.